

TRACSTAR® 630i

8" IPS - 24" OD (225MM - 630MM)



MADE FOR

UNDERGROUND
CONSTRUCTION



The next generation of TracStar® machines offers the industry a sophisticated, rugged, and productive fusion machine. Numerous improvements have advanced the level of technology available while simultaneously hardening that technology to make the entire fusion experience more reliable. The TracStar /Series features new emissions-compliant engines, a CAN bus control system, along with numerous hydraulic, mechanical, and electrical upgrades. Integrated, software-controlled machine options from manual to fully automatic improves operator consistency and adherence to standards.

ADDITIONAL IMAGES



STANDARD FEATURES

- ✓ Integrated DataLogger tablet records the entire fusion process
- ✓ FusionGuide™ Control System allows operators to choose their preferred level of software interaction while guiding them through the fusion process
- ✓ Self-contained, self-propelled, all-terrain
- ✓ Patented Centerline Guidance System for equal distribution of force around the joint
- ✓ CAN BUS system and touchscreen allow better machine diagnostics and troubleshooting
- ✓ Electronic keypads and paddles provide better control
- ✓ Redesigned cowling allows for fusion of tees and fittings without carriage removal
- ✓ Stage V- and Stage IIIA- compliant Perkins engine meets environmental requirements, generates less noise, offers greater torque for load response
- ✓ Removable 3- or 4-jaw carriage for in-ditch use
- ✓ On-board generator for powering heater
- ✓ Dual hydraulic pipe lifts aid in loading and unloading pipe
- ✓ Hydraulic pivoting heater and face with collision-avoidance sensors to prevent damage
- ✓ Wireless Remote Control ensures safe efficient working environment and precise machine placement
- ✓ Advanced blade design for smooth face and long life
- ✓ Self-locking brakes
- ✓ Variable Speed Tracks
- ✓ GFCI has been replaced with a PCM (Power Control Module) to reduce false trips
- ✓ Hydraulic hardlines replace hydraulic hoses for reduced leak points



DataLogger
COMPATIBLE

SEE SECOND PAGE FOR DETAILED SPECIFICATIONS

TRACSTAR® 630i

8" IPS - 24" OD (225MM - 630MM)

SPECIFICATIONS

MODELS		ENGINE		MACHINE DIMENSIONS	
AT24P0817487	High Force, Tier 4/Stage 5 Compliant	High Sulfur Vehicle Engine Horse Power	100 HP	Machine Length	150" (3,810mm)
AT24P0888656	High Force, High Sulfur Diesel			Machine Width	95" (2,413mm)
AT24P0888638	Medium Force, Tier 4/Stage 5 Compliant	Standard Vehicle Engine Horse Power	74 HP	Machine Height	80" (2,032mm)
AT24P0888654	Medium Force, High Sulfur Diesel			CARRIAGE DIMENSIONS	
WEIGHTS		Engine Fuel Type	Diesel	Length	4-Jaw - 91" (2,311.4mm) 3-Jaw - 62" (1,574.8mm)
Machine	9,700 lbs. (4,399.8 Kg)	Engine Fuel Tank Capacity	23 Gallons (87.1 Liters)	Width	4-Jaw - 68" (1,727.2mm) 3-Jaw - 51" (1,295.4mm)
Vehicle	6,100 lbs. (2,766.9 Kg)	Engine Operational Fuel Tank Capacity	18 Hours	Height	4-Jaw - 51" (1,295.4mm) 3-Jaw - 41" (1,041.4mm)
Carriage	4-Jaw - 3,600 lbs. (1,632.9 Kg) 3-Jaw - 1,400 lbs. (635 Kg)	Engine Starting System	Electric	SHIPPING DIMENSIONS	
Heater	240 lbs. (108.9 Kg)	POWER	220-240V, 10,950 Watts, 50 / 60 Hz	Length	150" (3,810 mm)
Facer	390 lbs. (176.9 Kg)			Width	95" (2,413 mm)
Shipping Weight	10,125 lbs. (4,592.6 Kg)	Heater		Height	80" (2,032 mm)
HYDRAULICS		Facer		INCLUDES	
System Pressure	3,250 PSI (224.1 BAR)	Facer	Hydraulic	Fusion machine, DataLogger® 7 tablet, facer, heater, remote control with rechargeable batteries and lifting assembly.	
Fusion Pressure	3,000 PSI (206.8 BAR)	CHASSIS			
Hydraulic Reservoir Capacity	23 Gallons (87.1 Liters)	Frame	Welded steel construction		
		Brake	Self-locking		
		MOBILITY			
		Mobility Type	Rubber crawler tracks		
		Transportation	Self-propelled		
		Vehicle Speed	1.5 MPH		
		Lifting	Lift points and lifting assembly		
		Starting System	Electric		